

# AR100 TWIN



30 years of experience  
Domestic water treatment  
and industrial.



The automatic control valve made of Noryl (insensitive to limescale and particles), is designed as the main control center for directing and regulating all cycles of a water softener.

The AR100 TWIN control valve is used to make a DUPLEX softener (2 bottles of resin).

Its design allows to obtain fresh water 24h / 24h. Recommended for professional use or consumption are very irregular.

AR100TWIN	20	30	50	70	90	120
Qt resin	2x20	2x30	2x50	2x70	2x90	2x120
2 Bottles	8x35	9x35	10x35	13x54	13x54	14x65
Salt tray vol.	200	200	200	200	200	300
Tray diam x ht	53x100	53x100	53x100	53x100	53x100	77x101
Ht tot.	111	111	111	1590	1590	1855
Capacity m3°F	2x100	2x150	2x250	2x380	2x450	2x600
Debit m3/h	5	5,5	5,5	5,5	5,5	5,5
Conso salt kg	2,8	4,2	7,0	9,8	12,6	16,8
Connection $\nabla$	4/4	4/4	4,4	4,4	4/4	4/4
Pres.max bar	8,4	8,4	8,4	8,4	8,4	8,4
Temp.max°C	43	43	43	43	43	43

